



LDT520

Laser Digital Theodolite

The World's Longest Laser Range* - 600 m (2,000 ft.).
For Directional Controls in Tunnel Excavation, Precise Marking and Alignment
in Construction and Engineering Applications.

* Compared to existing laser theodolites, as of October 1, 2008.

- Emits both a focused beam and a parallel beam
- Variable laser output
- Precision angle measurement
- Maximum dust- and water-protection



LDT520

Laser Digital Theodolite

The LDT520 drastically enhances productivity thanks to the high-brightness, high-precision laser beam as well as the versatility to emit both focused and parallel beams.

World's longest laser beam range for a digital theodolite*

- Offers 600 m (2,000 ft.) of laser beam range in tunnels or other underground sites**.
- The parallel beam reaches 200 m (660 ft.).

*As of October 1, 2008. ** Brightness of surrounding environment: 100 lx with focused beam at beam output of 4.5 mW.

One instrument for the focused beam and parallel beam

- Focused beam: Beam spot becomes the smallest at the focused distance of a telescope.
- Parallel beam: The beam diameter is constant in any distance, ideal for directional controls in tunnel construction.



- Parallel beam can be emitted by adjusting focusing ring to the ▼ mark, without the need for any accessory.

Variable laser output

- Easy adjustment of laser output power between 1 mW to 4.5 mW.

An advanced angle measurement system for optimum reliability

- Original absolute encoders employ advanced coding technology and the latest in digital processing technology.
- Provides exceptional precision and reliability under harsh construction environment.

Dual-axis compensation for maximum angle precision

- Automatically detects the instrument tilt in two directions.
- Compensates for both horizontal and vertical angles to ensure highly accurate angle measurement.

Slope display in % and ‰

- Vertical angle display can be switched to slope in per-cent (%) or per-mil (‰).

Highest in its class dust- and water-protection

- Conforms to the IP66 dust- and water-protection standard.
- Withstands the harshest conditions in the dusty or moist underground construction sites.



Operable in tight spaces

- Minimum focus of the optical plummet is as short as 15 cm (5.9 in.) from the tribrach bottom.
- This means the LDT520 can be precisely set at 15 cm above the reference point.

Product names mentioned in this brochure are trademarks of their respective holders.
Product colors in this brochure may vary slightly from those of actual products owing to limitations of the printing process.
Designs and specifications are subject to change without notice.

LDT520 Specifications

Laser			
Light source / Wavelength	Laser diode / 635 nm		
Output power	1 to 4.5 mW, variable. Adjusted with softkey.		
Laser class*1	Class 3R		
Laser focusing	Simultaneous with telescope focusing. Parallel beam is generated when the focusing ring is adjusted to the ▼ mark		
Measuring range*2	Over 200 m (656 ft.) / 1 mW laser output, Over 600 m (1,960 ft.) / 4.5 mW laser output		
Beam Spot diameter	Distance	focused Beam Diameter*3	Parallel Beam Diameter
	5 m (16 ft.)	φ 0.5 mm (0.02 in.)	φ 15.0 mm (0.59 in.)
	20 m (66 ft.)	φ 2.1 mm (0.08 in.)	φ 15.1 mm (0.59 in.)
	50 m (164 ft.)	φ 5.2 mm (0.20 in.)	φ 15.2 mm (0.59 in.)
	100 m (328 ft.)	φ 10.3 mm (0.41 in.)	φ 15.3 mm (0.60 in.)
	150 m (492 ft.)	φ 15.5 mm (0.61 in.)	φ 15.5 mm (0.61 in.)
	200 m (656 ft.)	φ 20.7 mm (0.81 in.)	φ 25.7 mm (1.01 in.)
	300 m (984 ft.)	φ 31.0 mm (1.22 in.)	
	400 m (1,312 ft.)	φ 41.3 mm (1.63 in.)	
500 m (1,640 ft.)	φ 51.6 mm (2.03 in.)		
600 m (1,960 ft.)	φ 62.0 mm (2.44 in.)		
Beam angle adjustment function	Built-in		
Laser ON / OFF	Switched with softkey		
Telescope			
Telescope	Length: 160 mm (6.3 in.), Objective aperture: 42 mm (1.7 in.), Magnification: 30x, Resolving power: 3", Field of view: 1°30' (26 m@1,000 m), Minimum focus: 1.3 m (4.3 ft.)		
Reticle illumination	Built-in (bright or dim, selectable)		
Angle measurement			
Type	Absolute rotary encoder scanning, Both circles adopt diametrical detection		
Unit	Degree/Gon/Mil, selectable		
Display resolutions	1" / 5", 0.0002 gon / 0.001 gon, 0.005 mil / 0.02 mil, selectable		
Accuracy (ISO17123-3:2001)	5" (1.5 mgon) (0.025 mil)		
Measuring time	0.5 s or less, continuous		
Measuring mode	H Clockwise / Counterclockwise, selectable. 0 set, Hold, Angle input, Repetition, available mode V Zenith 0, Horizontal 0, Horizontal 0±, Slope in % / ‰, selectable		
Automatic dual-axis compensator	Dual-axis liquid tilt sensor, working range: ±3", "Out-of-range" warning display and audible tone		
Collimation compensation	ON / OFF, selectable		
General			
Display	LCD graphic display, 192 x 80 dots, screen size: 71.5 x 31mm, with backlight and 16 contrast levels		
Keyboard	4 softkeys and 11 keys (total 15 keys)		
Control panel layout	On both faces		
Interface	Asynchronous serial, RS-232C compatible, baud rate: 1,200 to 38,400 bps		
Sensitivity of levels	Plate level: 40" / 2 mm, Circular level: 10" / 2 mm		
Optical plummet	Image: Erect, Magnification: 3x, Minimum focus: 0.15 m (5.9 in.) from tribrach bottom		
Tribrach	Detachable		
Dust and water protection	IP66 (IEC60529:2001) (EDC119A external power cable connection maintains IP66)		
Operation temperature	-20 to +50°C (-4 to +122°F)		
Storage temperature	-30 to +70°C (-22 to +158°F)		
Instrument height	236 mm (9.3 in.) from tribrach bottom		
Size (with handle and battery)	W 165 x D 165 x H 355 mm (W 6.5 x D 6.5 x H 14 in.)		
Weight (with handle and battery)	5.8 kg (12.8 lb.)		
Power supply			
Battery	BDC46B	Li-ion rechargeable battery, 7.2 V, 2.45 Ah, 103 g (3.6 oz.), 2 pcs. included.	
	Continuous use at 25°C (77°F)	Approx. 12.5 hours/ Laser output 4.5 mW and angle measurement	
		Approx. 13.5 hours/ Laser output 1 mW and angle measurement	
		Approx. 20 hours/ Angle measurement only	
Remaining battery level display	4 levels + Low level message		
Automatic power cut-off	5 / 10 / 15 / 30 minutes after operation / Off, selectable		

*1 IEC60825-1 Ed. 2.0: 2007 / FDA CDRH 21 CFR Part 1040.10 and 1040.11 (Complies with FDA performance standards for laser products except for deviations pursuant to Laser Notice No. 50, dated June 24, 2007.

*2 Brightness: 100 lx or less. Range may vary depending on atmospheric conditions.

*3 Theoretical diameter values for 0-order diffraction beams.

Standard Accessories

- BDC46B rechargeable battery : 2 pcs.
- CDC68 quick charger with EDC113A/113B/113C power cable
- CP7 tubular compass
- Lens hood
- Lens cap
- Plumb bob
- Tool kit
- Operator's manual
- Laser caution sign
- Carrying case and shoulder strap

Optional accessories

- BDC60 / 61 external battery
- EDC119A waterproof cable for BDC60 / 61
- EDC119 cable for BDC60 / 61
- EDC14 external battery adapter, EDC5 car battery cable for EDC14, EDC4 car cigarette lighter cable for EDC14
- DEC25 diagonal eyepiece
- LAP1 laser plummet
- DDC25 (25-pins, male), DDC26 (25-pins, female), DDC 27 (9-pins, female), DDC1 (tw/o connector) interface cables

* For more details, please consult your local sales representative.

www.sokkia.co.jp

SALES DEPARTMENT
75-1, HASUNUMA-CHO, ITABASHI-KU, TOKYO, 174-8580 JAPAN
PHONE +81-3-3558-2936 FAX +81-3-5970-2386